
ROTORDRONE PRO PRINT AD SPECS



PRINT AD SIZES

| Sizes | Width | Height |
|--|--------|---------|
| Spread—With 1/8" bleed on all sides | 16.25" | 11.125" |
| Spread-Non-Bleed | 15" | 10" |
| Full Page—Non-Bleed | 7" | 10" |
| Full Page—With 1/8" bleed on all sides | 8.25" | 11.125" |
| 2/3 Page | 4.625" | 10" |
| 1/2 Page (V) | 4.625" | 7.375" |
| 1/2 Page (H) | 7" | 4.875" |
| 1/3 Page (V) | 2.25" | 10" |
| 1/3 Page (S) | 4.625" | 4.875" |
| 1/4 Page (H) | 7" | 2.375" |
| 1/4 Page (V) | 2.25" | 7.375" |
| 1/6 Page (H) | 4.625" | 2.375" |
| 1/6 Page (V) | 2.25" | 4.875" |

H = Horizontal, V = Vertical, S = Square



AD SPECS FOR PRINT

PRINTING PROCESS:

BINDING PROCESS:

Web Offset

Saddle Stitch

REQUIRED AD MATERIAL:

File Info: 300 dpi PDF files created to PDF/X-1a settings strongly preferred.

Ad Sizes: Please adhere to Air Age Media Ad Size requirements when building your ad files.

Fonts: All fonts must be embedded in the file.

Safety Area: On all ads with bleeds, keep critical content 3/8" or more from the trim and gutter.

Knockout type: You must make sure your font size and thickness is sufficient for type that is knocking out of image and colors.

Black type: Should always be set to 100K (100K, 40C for rich black) and set to overprint.

Coloration: All color data must be CMYK. The file should not contain any RGB, LAB, etc. Maximum combined density must not exceed 290%. Material should be prepared to SWOP (Specifications for Web Offset Publications) standards.

AD FILE DUE DATES:

In order for Air Age to properly review ad file materials, it is important for our advertisers to adhere to Air Age Media's Ad Material Due Dates. Please contact **production@airage.com** or your Air Age Media sales representative if you need a list of our Ad Closing and Due Dates.

PROOFS:

Hard Proofs are not required. If you do send a proof it must be made to SWOP standards and received by the material due date.

EMAIL:

Files up to 25MB can be emailed to production@airage.com (large files should be zipped) FOR FTP INFORMATION CONTACT:

Production (203) 529-4604 production@airage.com

